


6-Strand Breakout Fiber Cables

10G OM3 MM or SM, with LC Connectors

Features and Applications



- Single Mode 9/125um and 10G OM3 Multimode 50/125um fiber options
- Strong 2.0mm Breakout OD, 8.0mm trunk OD for increased durability for indoor/outdoor
- Available in Standard LC connectors
- Ideal for equipment interconnect, telecom network, security connections, high speed data transfer and semi-harsh industrial applications

Optical Specifications

Fiber Type	Insertion Loss	Return Loss	Fiber Count	Operating Temperature Range
50/125um multimode	≤0.30dB	≥ 50dB	6	-40 ~ 70° C
9/125um single mode	≤0.30dB	≥ 50dB	6	-40 ~ 70° C


- Subject to change with or without notice.

Mechanical Specifications

Cable Configuration	Fan-out Length	Minimum Bend Radius	Jacket Material
Fan-out inline to Fan-out inline	0.5 meter	10D statis/20D dynamic (mm)	PE

Ordering Information

End A		End B		Fiber Type				Length (meter)	Pulling Tube
LC	-	LC	-	M= 50 /125um, MM	-	B6	-	001 = 1 meter	Blank = none
				S = 9/125um, SM				015 = 15 meter	PA= on End A
								100 = 100 meter	PB= on End B



For more information, please contact us at +1 949-305-6622, email: info@Phrontier-tech.com